

Big Systems, LLC N59 W14053 Bobolink Avenue

Menomonee Falls, WI 53051-5901

sales
solutions
supplies
support

888.244.4177 | 262.703.9000 | fax: 262.703.9009



HP Site Preparation

page 1 of 2

Pre-Installation Fax Back Checklist

Fax: 262.703.9009

Thank you for ordering your equipment from Big Systems LLC

TO FACILITATE A SMOOTH AND TIME-EFFICIENT INSTALLATION, PLEASE REVIEW THIS CHECKLIST CAREFULLY.

Please take a few minutes to fill out this form and fax it back to our offices @ 262-703-9009

THIS FORM MUST BE RETURNED TO US COMPLETED IN ORDER TO SCHEDULE YOUR INSTALLATION.

Please direct any questions to our technical support staff @ 262-703-9000

For Big Systems internal use only:	In stallation Data	
Company Name	Phone Printer Serial #	
Contact Name		
Printer Model		
Laminator Model		
RIP Server	RIP Server Serial #	
Castian 1 DID Camana an Duinean		
Section 1 - RIP Server or Drivers		
RIP Server PC w/DVD supplied by Customer	Big Systems Certified Design Station	
RIP Software Viper Raptor Talon I will be using the bundled version with HP L300) Series	
	d for the HP Z or T series	
I will be using another RIP software		
Your RIP OS should be Windows® 7 (32-bit or 64-bit) versions or Windo		
Security Center and personal software Firewall should be disabled. Add		
Section 2 - Networking		
We have two network connections. One for the PC and one f	for the Printer Yes No	
Mimaki's communicate via USB. Only 1 network connection is need		
connection on the Mimaki is on the right side of the printer and yo		
We will supply our own Ethernet Category 5e or 6 cables to t Yes (If custom made, they must be tested before	·	
	: Installation)	
No, BSI to provide cables at additional charge Lengths required		
We understand the printer needs a static IP address. IP address.		
We are connecting Mac's to print to the Static IP address for the RIP is required. IP addre		
The RIP software requires Administrator privileges. The installer needs to know this available. User accounts for the RIP workstation also require an Admin lo that having an Admin logon for the PC does not mean Admin rights to your n	v the admin logon and password if installing on your PC. Please have gon. Make certain your operator has these privileges. Remember	
Your IT Department should be on call for the installation.		



Big Systems, LLC N59 W14053 Bobolink Avenue Menomonee Falls, WI 53051-5901

888.244.4177 | 262.703.9000 | fax: 262.703.9009





HP Site Preparation

page **2** of 2

Fax: 262.703.9009

Pre-Installation Fax Back Checklist

Section 3 - Power		
For HP Designjet T Series For HP Designjet Z Series	110v standard plug	
For HP Designjet L Series	The printer has two power connectors that meet the following requirements. 200-240 volt, 20amp	VVall socket outlet
For HP Designjet FB Series	200-240v, 20amp single phase with NEMA L6-20R lock	ing wall receptacle.
		Receptocle
If stairs are to be used to tr	ound Level Entry Liftgate Required (additional charge vator be used to transport equipment to a floor other than stransport the equipment to a different floor, you must provide arking for our Technical Staff? Yes No	reet level? Yes No
Immediately repunpack the system ships with a quick location. Our tech for the printer to n	ral it is important to inspect the shipment for any damages that mort any freight damages to the carrier prior to acceptance of delays in in the event there are any obvious damages or missing items prior to setup guide. The printer should be assembled and placed on its stance in its staff will perform the initial ink charging, prep, configuration set in a first print at installation. If there are any questions when in specific moved to the general area for installation. Our techs need room to make it?	ivery. It is also important to o installation. Your system I (if applicable) in the production ttings and calibrations necessary ecting or assembly, just call us!
Section 5 - Printe Please select how your printer(s)	r Connectivity) are to be connected in your workflow environment:	
For HP Designjet T Series	USB v2.0	We need a cable.
For HP Designjet Z Series For HP Designjet L & FB Series	100/1000bT Ethernet	We need a cable.
Cables and printer accessories Special note regarding Etherne	are available at additional cost. Industry standards limit USB lengths et connectivity: 801.11a/b/q wireless Ethernet is not recommended!	to 15 feet from printer.



Big Systems, LLC N59 W14053 Bobolink Avenue Menomonee Falls, WI 53051-5901

888.244.4177 | 262.703.9000 | fax: 262.703.9009





Fax: 262.703.9009

Post Installation Handy Reference Sheet

Certificate of Installation

Delivery & Acceptance, Check

Equipment Model / 9	Serial Numbers
Company Name	Installation Date
Contact Name	Phone
Printer Model	Printer Serial #
Laminator Model	Laminator Serial #
DID Correct	RIP Server Serial #
Network & RIP Settii	ngs
Printer static IP address	Subnet Gateway (if used)
RIP printer name	RIP share name
RIP default media	Ink mode/configuration
Printer static IP address	Subnet Gateway (if used)
	RIP share name
	Ink mode/configuration
Printer static IP address	Subnet Gateway (if used)
	Substict RIP share name
	Ink mode/configuration
RIP software settings:	
	Product Version Build rev
•	versionbuild rev
RIP server settings:	
DHCP	
—	Subnet
	DNS
Domain or	¬
	Two regroup realite
Dedicated second	
Static IP	Subnet
Gateway	DNS
—	

Primary customer contact _